

6/PRTS

09/786739
2 Rec'd PCT/PTO 08 MAR 2001

WO 00/14355

PCT/NZ99/00149

BUILDING FRAME AND METHOD OF CONSTRUCTION

FIELD OF INVENTION

5

This invention relates to metal framing, in particular steel framing, for building construction. The invention also relates to a method of constructing a metal frame assembly and apparatus for producing metal framing for building construction.

10

BACKGROUND OF INVENTION

The high costs of timber have made the use of steel framing in building construction cost effective. Known forms of steel frame construction require the riveting together of frame members which make up the studs and nogs of the frame. Since the frame members generally have a C-section it is necessary to bend back the lip at various points along a stud where a nog is to be interconnected. This bending out or flattening of the lip can introduce bending or deformation of the frame member. Furthermore, because all components of a frame are made from members of the same cross-section, the required overlapping of members when a nog is inserted between the sides of a stud results in localised deformation of the stud. Any deformations in the sides of the frame members results in an uneven planar surface of the frame with consequential difficulties in affixing a cladding to the frame with a preferred even finish.

25

A further limitation associated with conventional methods of constructing steel framing for building relates to the fact that the framing is manufactured off site in standard lengths. The construction of a frame from such preformed lengths at a construction site is labour intensive and therefore costly. Each standard piece has to be manually cut, punched and assembled on site.

30

09/786739 406464

It is an object of the present invention to provide a method of manufacture of a metal frame section for building construction and/or a method of constructing a metal frame assembly for building construction and/or apparatus for forming metal frame sections, which reduces or overcomes the abovementioned problems, or
5 which at least provides the public with a useful alternative.

Other objects of the invention may become apparent from the following description which is given by way of example only.

10 SUMMARY OF INVENTION

According to one aspect of the present invention there is provided roll forming apparatus adapted to form, from sheet metal strip, metal frame members for use in building construction, said apparatus including lip forming members
15 engageable to convert a roll-formed U-section channel profile to a C-section channel profile, and said apparatus adapted to form the said U-section and C-section channel profiles simultaneously on the same sheet metal strip.

Preferably, the roll forming apparatus may further be adapted to roll form
20 different widths of channel profile at selected regions during a continuous roll forming operation.

Preferably the apparatus may further include a moveable operational unit including one or more functional components.
25

Preferably the apparatus may further include computing means adapted to control and synchronise roll forming, lip-forming, groove-forming and the operational unit.

30 According to a further aspect of the present invention there is provided a method of constructing a building frame assembly said method including the steps of:

- recording data defining a unit area in which the frame assembly is to fit,

00795739 104504
FOR OFFICIAL USE

- processing the data on computing means to design the frame assembly to fit the unit area,
- controlling operation of roll forming apparatus adapted to form channel-shaped metal frame members from sheet metal strip, using the processed data from the computing means, to produce frame members cut and formed ready for assembly to produce the required design of frame assembly.

According to a further aspect of the present invention there is provided a frame assembly for use in building construction, the assembly including a plurality of metal frame members, portions of selected frame members having a U-section channel profile swaged or narrowed portion adapted to engage within the sides of a U-section channel profile of another frame member substantially without deforming the profile of the other frame member.

Preferably, the frame assembly may include a plurality of first metal frame members forming studs and a plurality of second metal frame members forming nogs.

According to a further aspect of the invention there is provided a method of constructing a metal frame member from a sheet metal strip on roll forming apparatus, the method including forming U-section and C-section channel profiles simultaneously on the same sheet metal strip.

Other aspects of the present invention may become apparent from the following description which is given by way of example only and with reference to the accompanying drawings.

BRIEF DESCRIPTION OF DRAWINGS

Figure 1:

Shows a perspective view of a junction between nogs and a stud of a metal frame assembly of the present invention, in one form;

Figure 2:

Shows a junction between an end of a stud and a base plate, or an end of a nog and a stud, of a metal frame assembly of the present invention;

5

Figure 3:

Shows a nog of an assembly of the invention in one preferred form;

Figure 4:

Shows a perspective view of a junction between nogs and a stud of a metal frame assembly of the invention in an alternative preferred form;

10

Figure 5:

Shows a schematic representation of roll forming apparatus of the present invention in one preferred form.

15

Figure 6:

Is a flow diagram of the steps involved in a method of the invention for producing a metal frame assembly.

20 **DETAILED DESCRIPTION OF INVENTION**

This invention has several aspects all directed towards the efficient construction of metal frame assemblies. Hereafter, such assemblies and their components are referred to as steel frame members or assemblies since steel is the current metal of choice. However, it will be appreciated that other metals or alloys may be used.

25

The first aspect of the invention relates to a method of construction of steel frame members in a form which facilitates assembly of the frame and which enables a frame to be produced with substantially planar surfaces. This is achieved by using roll forming apparatus to produce the steel frame channel members with a U-cross-section and forming this into a C-cross-section only at portions between or free from intended junctions. It is further facilitated by including one or more longitudinal

30

5

10

15

20

25

30

adapted to engage within the stud channel. Figure 4 shows an assembly in this configuration.

Holes may have been prepunched through the sides of the stud and nogs to
5 receive rivets 15 which securely engage the components of the assembly together.
Recesses or dimples 16 may also be preformed in the outer surface of the stud, about
the punched hole so that a rivet head is recessed or substantially flush with the stud
side surface.

10 With this design of assembly there is no deformation of the sides of the stud
at the regions of interconnection with nogs, ensuring that cladding applied to the
surface of a constructed frame will have an even finish.

Figure 2 shows the connection between the bottom of a stud 20 and a base
15 plate 21, although this could equally represent interconnection of the nog 3 of Figure
1 into its stud 2. It can be seen that the base plate 21 differs from the stud 20
primarily in having a C-section along its entire length, there being no requirement
for the strengthening achieved by rolling to form a C-section. The U-section end 22
of the stud 20 is narrowed or swaged to engage within the base plate 21 without
20 deforming the sides of the base plate.

The narrowing or swaging of ends of frame members is achieved in the
process of manufacturing each section by increasing the depth of the ridges 10.

25 A second main aspect of the invention relates to the method by which the
individual components of a required frame assembly are manufactured. This is
achieved by use of roll forming apparatus adapted to produce frame members of the
desired configuration from galvanised flat steel in coil form. The roll forming
apparatus may be portable so as to be located at a construction site. Alternatively,
30 the roll forming apparatus may be located at a central manufacturing site, with
information for specific jobs downloaded directly to the apparatus.

097967391004
T033T06236260

With reference to Figure 5, the roll former 41 includes a first set of rollers 42 adapted to convert the flat steel 43 from the coil 44 into a U-shaped channel. Lip rollers 45 are provided to convert parts of the U-shaped channel into a C-section. Swage rollers 46 introduce the ridges in the base of the channel, and are adapted to control the depth of the ridges.

The apparatus may include two sets of lip rollers, the first to form a lip at substantially 45° and the second to continue the lip to substantially 90°, in relation to the channel sides.

10

A moving tool bed or operational unit 47 is provided. This servo-controlled tool bed may include a slitter 48 for producing slits in the sides of the base of the channel at the regions of intended interconnection, a service hole punch 49 adapted for producing holes for electrical wires, plumbing pipes and the like, a notcher 50 for removing a section of the base of the channel which then leaves protruding side portions of a nog for engagement in a stud, and a guillotine and hole punch unit 51 for punching and optionally counter-sinking rivet holes and guillotining each frame member to length. The servo-controlled system enables these functions to be carried out during continuous feed of the steel through the apparatus. It will be appreciated that more or less features may be included on the servo table; for example the slitter may be omitted.

At least one set of the first rollers 42 may be knurling rollers 53 adapted to form textured outer sides of the U-channel. The knurling of the sides of the channel assists in preventing screws from slipping when applying a cladding such as gypsum plasterboard to a completed assembly.

The roll forming apparatus 41 is adapted to produce U-shaped and C-shaped section simultaneously by control of the lip rolling function. This enables framing sections to be produced which do not require flattening of lip portions to enable interconnection of the end of one member within the channel of another. Similarly, the swaging or narrowing of profile at desired regions can be achieved within the single roll former in a continuous operation.

PCT/NZ99/00149

The roll forming apparatus is controlled by computing means.

The roll forming apparatus may be driven by hydraulic motor or
5 alternatively by an electric motor. It is preferably adapted to roll from 0.4 to 1.2
millimetre gauge steel or galvanised steel.

Optionally, the roll former may also include a straightening station,
comprising vertically disposed pairs of rollers about each side wall for lateral
10 straightness and a pair of horizontally disposed rollers for vertical straightness, to
ensure that each frame member is straight. Flat steel in coil form is not always
straight, and this can result in bends or warps in individual lengths of building
elements.

15 A preferred method of producing a building frame assembly of the invention
is now described with reference to Figure 6.

The measurements of a space for which a frame assembly is required is
taken on site manually, or automatically by a laser measuring device. This data is
20 entered into a computing means such as a palm-top or notebook computer. Also
loaded into the computer are details from the architectural plans. Where
architectural plans are available in electronic form, the on site data is used for
verification.

25 The data is processed using specific software to generate a required frame
design for that space. This design will include not only the dimensions of the space
but also the locations and dimensions of architectural and other features required to
be accommodated in the space, such as windows, doors, air-conditioning ducts,
electrical sockets and switches and the like. The frame assembly outline is then
30 downloaded via cellphone or an internet link, for example, to the factory site where
the rollformer is located. The rollformer computer controls all operations of the
rollformer to produce the frame members required for the frame assembly. Thus, the
length and configuration or form of each frame member for this frame assembly are

calculated by the computer; which in turn controls operation of the roll former to form each required frame member from the flat steel coil in a substantially continuous operation.

5 Thus, by employing the method of the present invention involving the roll forming apparatus described, customised frame assemblies to fit spaces having specified design characteristics can be manufactured and constructed conveniently and efficiently. Effectively a kit set of frame members is provided for each required building frame assembly. This avoids the problems associated with the use of
10 standard preformed steel frame members which must be manually cut, punched and forced together in a manner which often results in the deformation of the smooth surfaces to which cladding must be applied.

 Where in the foregoing description reference has been made to specific
15 components or integers of the invention having known equivalents then such equivalents are herein incorporated as if individually set forth.

 Although this invention has been described by way of example and with reference to possible embodiments thereof it is to be understood that modifications
20 or improvements may be made thereto without departing from the scope or spirit of the invention.

FOUO 6629269